



## Polluce Magnum

### Movement

Anonimo Automatic Caliber 01.0 on Sellita SW200 or ETA 2824-2, with rotor designed on Anonimo specifications; 21 rubis, colimaçon finish, adjusted 4 positions, 28.800 A/h. Power reserve: about 40 hours.

### Functions

Hours, minutes, central seconds; date window at h. 4.

### Case

Watch case and bezel manufactured in UNI5275, a special bronze alloy, sand-blasted with satin finish, diameter mm. 43.40, maximum diameter at the protection crown tool mm. 45.60; UNI5272 belongs to the family of alloys (bronze alloyed with aluminium-iron-nickel) used in the development of nautical high tech tools provided with high mechanical and corrosion resistance, as well as in the utilisation of equipment such as high-performance propellers, bosses (pitch) for variable pitch propellers, torpedoes flanges. Back cover in AISI316 Plus stainless steel with satin finish. Back cover and bezel closure with Thorx external screws (9 in total) guaranteeing easier locking. Crown in stainless steel with screw locking, sized for easy grip, red-coloured tube for open crown alarm. Automatic valve, functioning based on external/internal pressure differential, to ensure the release of possible helium penetrated into the watch while attending professional hyperbaric chambers. Thick, rounded sapphire upper glass.

### Water Resistance

120 ATM.

### Dial

Large dimensions, extra thick dial, with hour indexes treated with luminescent material for high visibility night and day. Baton hands and thread sweep seconds hand treated with luminous coating. Date window at h. 4.

### Wrist Strap

Leather strap with Kodiak patented treatment for up to 24-hour continuous diving in salty water; Anonimo exclusive buckle in stainless steel.

